


# 1x4mm<sup>2</sup> Earthing Cable Yellow/Green (100m rolls) SE023

## DATA SHEET

<b>Standard</b>
RoHS EU Directive 2011/65/EU
<b>Style</b>
02(RV)
<b>Rating</b>
70°C 450/750V



Cable Construction		
<b>Conductor</b>	Size (mm <sup>2</sup> )	4.0mm <sup>2</sup>
	Cond. Size (mm)	52/0.30±0.008
	Material	Tinned Copper
	Stranded O.D (mm)	2.50
<b>Insulation</b>	Material	PVC
	Nominal O.D. (mm)	4.30±0.20
	Minimum Thickness (mm)	0.62
	Nominal Thickness (mm)	0.80

Electrical Properties	
Spark Test	6000V
Dielectric-withstand test	2500VAC/5min
Conductor resistance Max at 20°C	≤5.09Ω/km

Physical Properties	
Elongation of unaged values	≥125%
Tensile strength of unaged values	≥12.5Mpa

Marking
PGK DISTRIBUTION V90 EARTH CABLE 4MM2 450V/750V AS/NZS5000.2 >1< PGK00XXX PGK DISTRIBUTION V90 EARTH CABLE 4MM2 450V/750V AS/NZS5000.2 >2<PGK00XXX ..... >100< PGK00XXX

**Please Note:**

Please consult with your Electrician/Engineer to ensure suitability for the intended application and installation.

PGK Distribution takes every precaution to ensure the information in this publication is correct but accepts no liability of any kind and reserves the right to change any detail in this catalogue without notification.